

## Slip test results

## **DKR142-H**

Solid Brass Stair Nosing with Carb Insert



A division of Safe Environments Pty Ltd www.SafeEnvironments.com.au

4/40 Bessemer Street Blacktown NSW 2148 Phone 02 9621 3706 ABN 80 118 534 768

4 April 2016

## Test Report No. R8667

Slip Resistance Classification of New Pedestrian Surface Materials AS 4586:2013 Appendix A (Wet Pendulum Test)

The slip resistance Classification has been determined for unused surfaces using specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface.

Requested by:

Tredfx / Classic Architectural

Client Address:

Product Manufacturer:

Preston VIC 3072 Supplied by Classic Architectural

Product Description:

Tredfx gritted anti-slip insert product, resin strip with silicon carbide grit surface AS 4586:2013 Appendix A

Test conducted according to: Location:

Conducted by:

Slip Check Pty Ltd Test Facilities, Blacktown NSW 2148

Temperature:

Sample: Rubber slider used:

Unfixed Slider 96 Cleaning: Conditioned:

Grade P 400 paper dry followed

Slope of specimen:

by wet lapping film

Direction of Test:

Tested on a flat level surface Perpendicular to ribbed surface

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	59	59	58	57	60

58	Reported SRV of Sample:
P5	Class:



Ryan Voorderhake Laboratory/Field Technician

Safe Environments Pty Ltd R8667 - Slip Check, Tredfx Gritted insert stairnosing products 4 April 2016